

Features



- **Lightweight steel frame can be folded to a compact 13" width for easy portability, transport and storage**
- Adjustable height, flip-up armrests
- Programmable Dynamic controller with common connectors
- Adjustable length controller mount can be affixed to either the left or right armrest and can be fitted with an optional swing-away arm
- Flat-free, non-marking tires
- Standard anti-tip wheels for added safety
- Standard seat belt and seat back storage pouch
- Swing-away footrests, aluminum footplates and calf strap
- Elevating leg rests available (sold separately)
- Padded, fold-down backrest and cushioned seat available in 18" and 20" widths
- Manual wheel locks for additional safety
- Batteries included



Frame Color

Black

Accessories

- Elevating Leg Rests
- Swingaway Controller Arm
- Armrest Bag

Specifications

Max Weight Capacity	300 lbs.	Power	
Max Speed	4 mph	Motor	Two 24V x 200W x 3900rpm
Max Range	20 miles	Controller	Dynamic A50A
Max Grade/Incline	12°	Batteries	Two DC12V x 36AH (UI)
Turning Radius	32"	Battery Charger	5 Amp, Offboard
Ground Clearance	4"	Brakes	Electromagnetic
Dimensions		Freewheel Mode	Yes
Overall Length	43"	Tires (Flat-free)	
Overall Width	26" (18" seat) 28" (20" seat)	Front Casters	8" x 2"
Floor to Seat Height	19"	Rear Drive Wheels	12.5" x 2.25"
Seat Dimensions		Weights	
Available Sizes	18"(w) x 16"(d) 20"(w) x 16"(d)	Without Batteries	92 lbs.
Back Height	19"	With Batteries	140 lbs.
Armrest to Seat Height	9.5"–13.5"	<i>Speed and range will vary according to user weight, terrain, battery charge/condition and tire pressure.</i>	



www.thescooterstoreonline.com
(800) 723-4535